

1 Product Description

An obliterating matt finish designed to fill surface imperfections in concrete block, poured concrete and plaster providing a sound base for subsequent coats or as a finish.



2 Properties

- Can be used in internal and semi-exposed areas where an even decorative coating is required
- Provides base for subsequent coats
- Non-hazardous and non-toxic
- Solvent and silicone-free
- Ready to use
- Can be applied by brush, roller or spray
- Non-flammable
- Drying time: 2 hours at 18°C and 65% humidity. Recoatable after 2-4 hours.
- Coverage approximately 10-12m² per litre on smooth surfaces. Rough surfaces will considerably reduce the spreading rate
- Available in 5 and 20 litre containers
- Colours - White
- Finish - Matt

3 Preparation

- Surfaces should be sound and dry and free from oil, wax, grease and loose particles

4 Application

- Stir thoroughly
- Use directly from the container; do not dilute
- Apply brush, roller or spray
- Do not apply when the temperature of the surfaces to be treated is below 5°C

5 Storage

Keep out of reach of children.
Protect from frost.

6 Clean Up

Clean tools and equipment immediately after use with warm, soapy water.

7 Health & Safety

Ensure adequate ventilation during application and drying. Keep out of reach of children. In case of contact with eyes, rinse immediately with clean water. After contact with skin, wash off immediately with soap and water or a recognised skin cleaner. Contains no added lead.

Technical Assistance

For technical advice and assistance please contact the **Muralplast Technical Office** on the number below.

Important

The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use individual cases. For more information, please see the Material Safety Data Sheet.